

Project name:	
Fixture type:	
Date:	

## 4" Chrome Reflector with Suspended Frosted Glass



#### **Features**

- Reflector with Suspended Frosted Glass.
- Lamp: 32W MAX CFL (PL-T) or 50W MAX PAR20, R20.
- O.D.: 4 7/8".

#### **Technical Details**

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



#### **Product Numbers**

Item	Finish
EL926B	All Black
EL926BZ	All Bronze
EL926N	Nickel
EL926W	All White
EL926G	Gold

#### Product Number Builder Example: EL926B

4" Reflector with Suspended Frosted Glass Finish

EL926

**B** All Black

**BZ** All Bronze

N Nickel

W All White

**G** Gold

# **Compatible** Products



For use with 4" Trims for PAR Lamps

## 4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction** 



4" Airtight Housing **New Construction** 




4" Airtight IC Housing **New Construction** 

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	
EL99A	

SPECIFICATIONS		
Lamp: 50W MAX.		

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction** 

FA	
PIE.	

4" Airtight IC 2-Hour Fire Rated Housing **New Construction** 

CAT NO.	SPECIFICATIONS
FL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

### 4" Accessories



Fire Cover



Fire Enclosure



M	ca	Fi	re	Ta	ре

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3%"

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L