

Project name:	
Fixture type:	
Date:	

6" Baffle with Regressed Fresnel Lens Trim



Features

- Regressed Fresnel Lens.
- Lamp: 60W MAX A19.
- O.D.: 7 1/4".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 6" Integrated LED Housings.

Lamp: Compatible with Medium base (E26) PAR type.

Options





Black w/White Trim

White

Bronze

Product Numbers

Item	Finish
ELM43B	Black with White Trim
ELM43BZ	All Bronze
ELM43W	All White

Product Number Builder Example: ELM43B

6" Regressed Fresnel Lens Trim

Finish

ELM43

- Black with White Trim
- BZ All Bronze
- W All White

Compatible Products



For use with 6" Trims for PAR Lamps

6"Line Voltage ICA Housings



6" Airtight IC Housing New Construction



6" Airtight IC Housing

Double Wall New Construction



6" Airtight IC 2-Hour Fire Rated Housing New Construction

CAT NO.	SPECIFICATIONS	
EL7ICA	90W, with Socket Bracket	
EL7ICANB	90W, without Socket Bracket	







6" Airtight IC Housing Remodel



6" Shallow Airtight IC Housing

New Construction

	1	
	. 4	2001
F 1		
10	The same	0

6" Shallow Airtight IC Housing Remodel

CAT NO.	SPECIFICATIONS	
EL7RICA	Lamp: 90W MAX.	

CAT NO.	SPECIFICATIONS
R9ICA	Lamp: 75W MAX.

CAT NO.	SPECIFICATIONS
RR9ICA	Lamp: 75W MAX.



6" Airtight IC Housing with GU24 Base Socket New Construction



6" Airtight IC Universal Housing New Construction



6" Airtight IC Universal Housing Remodel

CAT NO.	SPECIFICATIONS	
EL7ICA-G24	Lamp: 27W MAX.	

CAT NO.	SPECIFICATIONS
R10H	Lamp: 150W MAX.

CAT NO.	SPECIFICATIONS	
DD10H	Lamp: 150W MAX	



6" Shallow Housing New Construction

60	7	
15	0	00
1 2	- 1	-
100	12 000	

6" Shallow Housing Remodel

CAT NO.	SPECIFICATIONS
R9H	Lamp: 75W, Medium Base (E26)

CAT NO.	SPECIFICATIONS
RR9H	Lamp: 75W MAX.,
	Medium Base (E26)

Compatible Products



For use with 6" Trims for PAR Lamps

6" Accessories











Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 %" W

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L