

Project name:

Fixture type:

Date:

Ixia[™] LED Low Voltage Undercabinet Lightbar



Features

- CCT Tunable (3000K-6500K)
- Linkable up to 12 ft.
- Polycarbonate lens
- Aluminum finish
- Input 24VDC
- Dimmable with EUDCCT/EUDS1Mounting brackets included
- 5/8" H x 3/4" W

Specifications

| Wattage | 4.5W |
|-------------|-------------|
| Lumens | 260 lm |
| Voltage | 24 VDC |
| Color Temp. | 3000K-6500K |
| Dimmable | EUDCCT |
| Lamp Type | LED |
| | |

Product Number

| Item | Description | Lamp type | Lumens | сст | Watts | Voltage | Dimming | Finish |
|---------------------|-------------------------------|-----------------|--------|---------------------------------|-------|-----------------------|---------|---------------------------|
| EUN52W | 12" CCT Tunable | LED | 260 lm | 3000K-6500K | 4.5W | 24 VDC | EUDCCT | Aluminum |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| • • • • • • • • • • | • • • • • • • • • • • • • • • | • • • • • • • • | ••••• | • • • • • • • • • • • • • • • • | ••••• | • • • • • • • • • • • | | • • • • • • • • • • • • • |

Compatible Products

Ixia[®] LED Undercabinet Light



Accessories

CAT NO.

EUDCCT





SPECIFICATIONS

For EUN51-EUN53 only

.....

Linking Cable

SPECIFICATIONS

For EUN51-EUN56

CAT NO.

EUDC51



Dimmer Switch

CAT NO. SPECIFICATIONS EUDS1 For EUN54-EUN56 only



PIR Sensor Switch

CAT NO. SPECIFICATIONS EUDPH1 For EUN54-EUN56 only



Movement Sensor Switch

| CAT NO. | SPECIFICATIONS | 1 |
|---------|----------------------|---|
| EUDMS1 | For EUN54-EUN56 only | |



Input Connector

CAT NO. SPECIFICATIONS EUDPC For EUN54-EUN56 only



24V LED Driver with 6-Way Distributor

| CAT NO. | SPECIFICATIONS |
|-----------|-----------------|
| DRV24V30W | For EUN51-EUN56 |



Dimmer Compatibility Chart Undercabinet

EUD Series

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

| Manufacturer | Product | Part Number | Dimmed Light Output Range |
|--------------|---|-------------|---------------------------|
| 120V Only | | | |
| Legrand | CFL/LED Multi-way Paddle Dimmer | HDCL-453 | 10% - 100% |
| Leviton | IllumaTech Single Pole/3-Way Preset Electro-Mechanical Electronic Low Voltage Slide Dimmer | IPE04 | 10% - 100% |
| | Decora SureSlide® Single Pole/3-Way with Present ON/OFF Switch | 6674 | 5% - 90% |
| | Rotary Dim N Glo 600W 3-Way Dimmer | DNG-603PH | 10% - 100% |
| | DIVA® (Gloss) 450W, Single Pole, Magnetic Low Voltage Dimmer | DVLV-600P | 10% - 100% |
| Lutron | DIVA® Series 600W Single Pole Dimmer | DV-600P | 10% - 100% |
| | DIVA® Series 150W Single Pole/3-Way Dimmer | DVCL-153P | 5% - 86% |
| | Maestro® Series 150W Single Pole/3-Way/Multi-Location Dimmer | MACL-153M | 5% - 80% |
| | DIVA® (Gloss) 600W 3-Way Preset Eco-dim Dimmer | DV-603PG | 10% – 100% |

*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.