

3" Reflector Light Engine

The perfect lighting solution for high-end residential and light commercial projects.



Features

- High efficacy LED module.
- Triac/ELV/0-10V dimming.
- Must be used with ELCO 3" Cedar™ System Housings.
- Life span of 50,000 hours L70.
- USA designed and assembled.
- Limited 5 year warranty.
- 2 at the end of the item number denotes Generation 2.
Please note Gen 2 and Gen 1 are not cross compatible.

Specifications

| | |
|----------------------|---------|
| Wattage | 11W |
| Lumens | 1000 lm |
| Color Temp. | 2700K |
| Lamp Type | LED |
| Beam Angle | 60° |
| CRI | 93+ |
| Damp Location | Listed |

Options



All White



Black w/White Trim



Chrome w/White Square



Haze w/White Trim



All Bronze



All Black

Technical Details

Optics: Frosted polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

Trim Construction: Reflector is two piece trim for maximum color versatility. Design allows for minimal glare and a strong glare cut-off. Trim is constructed of metal for lasting durability.


Installation: Must be installed on a Cedar™ System housing with compatible lumen rating. Frames are available for New Construction and Remodel as IC or non-IC.

LED Technology:

- Extremely accurate Color Rendering Index of 93+.
- Efficacy of 97 lumens per watt.
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results.
- Superior Thermal Management by utilizing ELCO Red heat sink.
- Instant On to Full Brightness technology.
- No LED pixilation.

Sunset: Sunset color temperature is our dim-to-warm LED technology that allows the color temperature to become warmer as the product is dimmed. Our SUNSET items start at 3000K and go as low as 1800K when dimmed. For Sunset dim technology be sure to order an item with "Sunset" in the Color Temperature (CCT) attribute.

Listings: cUL Listed for Wet Location. RoHS Compliant.



Product Number Builder

Example: E320C0827W2

| | | | | | |
|----------------------------|------------|------------------------|--------------------------|------------|-------------|
| ELCO Cedar 3" Light Engine | Lumen | Color Temperature | Finish | Generation | Beam Angle |
| E320C | | | | | |
| | 08 850 lm | 27 2700K | W White | 2 Gen 2 | 60° lens |
| | 10 1000 lm | 30 3000K | B Black with White Trim | 1 Gen 1 | -F 38° lens |
| | | 35 3500K | C Chrome with White Trim | | -N 24° lens |
| | | 40 4000K | H Haze with White Trim | | -S 15° lens |
| | | 50 5000K | | | |
| | | SD Sunset ¹ | BZ All Bronze | | |
| | | | BB All Black | | |

¹ Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

Compatible Products

For use with 3" Cedar™ Light Engines

3" Cedar™ Dedicated LED ICA Housings



2-Hour Fire Rated
3" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E3FH | Up to 850lm |



3" ICA Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E3LC | Up to 850lm |



3" ICA Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E3LRC | Up to 850lm |

3" Cedar™ Dedicated LED Non-IC Housings



3" Non-IC Housing
New Construction

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E3LC | Up to 1000lm |



3" Non-IC Housing
Remodel

| CAT NO. | SPECIFICATIONS |
|---------|----------------|
| E3LRC | Up to 1000lm |

PRODUCT NUMBER BUILDER

| Housing Type | | Lumen | ICA Airtight | Dimming | Optional |
|----------------------|------------------|----------------------|------------------------|-----------------------------------|--|
| <input type="text"/> | | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| E3FH | Fire Rated | 08 850 lm | (Blank) Non-IC | (Blank) 120V Triac/ELV | EM1 Emergency Backup up to 700 lm output |
| E3LC | New Construction | 10 1000 lm | ICA IC Airtight | D 120/277V Triac/ELV/0-10V | EM2 Emergency Backup up to 1100 lm output |
| E3LRC | Remodel | | | L Lutron | |