

Project name:	
Fixture type:	
Date:	

4" Baffle Trim with Socket Bracket



Features

- Baffle Trim with Socket Bracket, 25-30° tilt.
- Lamp: 55W PAR16, 50W PAR20 or R20.
- O.D.: 4 3/4".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



Product Numbers

Item	Finish
EL995BZ	All Bronze
EL995CP	Copper
EL995N	Nickel
EL995W	All White
EL995B	Black with White Trim

Product Number Builder Example: EL995BZ

4" Baffle Trim with Socket Bracket Finish

EL995

BZ All Bronze

CP All Copper

N Nickel

W All White

B Black with White Trim

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**




4" Airtight IC Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	
EL99A	

SPECIFICATIONS	
Lamp: 50W MAX.	

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction**

FA	
PIE.	

4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS
FL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

4" Accessories



Fire Cover



Fire Enclosure



M	ca	Fi	re	Ta	ре

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3%"

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L