

4" Metal Step Baffle Trim with Socket Bracket



Features

- Baffle Trim.
- Integral Socket Bracket to control lamp height.
- Lamp: 40W MAX A19 or R16, 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

Technical Details

Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options



Black w/White Trim



White



Nickel



Black w/Nickel Trim



Nickel w/Black Trim



Nickel w/White Trim



Copper



Bronze

Product Numbers

Item	Finish
EL993KB	Black with White Trim
EL993KW	All White
EL993KN	Nickel
EL993KBN	Black with Nickel Trim
EL993KNB	Nickel with Black Trim
EL993KNW	Nickel with White Trim
EL993KCP	Copper
EL993KBZ	All Bronze

Product Number Builder

Example: EL993KB

4" Baffle Trim with Socket Bracket	Socket Bracket	Finish
EL993	<div><div>no Socket Bracket</div><div>K Socket Bracket</div></div>	<div><div>B Black w/White Ring</div><div>W All White</div><div>N All Nickel</div><div>BN Black with Nickel Trim</div><div>NB Nickel with Black Trim</div><div>NW Nickel with White Trim</div><div>CP All Copper</div><div>BZ All Bronze</div></div>

Compatible Products

For use with 4" Trims for PAR Lamps



4" Line Voltage ICA Housings



4" Airtight IC Housing
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing
New Construction


CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L