

# 4" Phenolic Step Baffle Trim



## Features

- Phenolic Step, Metal Ring.
- Lamp: 32W MAX CFL (PL-T) or 50W MAX PAR20 or R20.
- O.D.: 4 3/4".

## Technical Details

### Construction:

- Meticulously manufactured trim with a powder coated or anodized finish.
- Baffle helps reduce glare.

**Installation:** Clips securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 4"Line Voltage IC and Non-IC versions.

**Lamp:** Compatible with Medium base (E26) PAR type.

## Options



All White



Black w/White Trim



All Bronze



All Nickel



All Black



Black w/Nickel Ring



White w/Nickel Trim



Nickel w/White Trim



Black w/Bronze Trim



Bronze w/White Trim



White w/Bronze Trim

## Product Number

Item	Finish
EL993BZ	All Bronze

4" Phenolic Baffle Metal Trim

Finish

EL993	
-------	--

B

Black with White Trim

BZ

All Bronze

W

All White

N

All Nickel

BB

All Black

BN

Black with Nickel Trim

WN

White with Nickel Trim

NW

Nickel with White Trim

BBZ

Black with Bronze Trim

BZW

Bronze with White Trim

WBZ

White with Bronze Trim

# Compatible Products

For use with 4" Trims for PAR Lamps



## 4" Line Voltage ICA Housings



4" Airtight IC Housing  
Double Wall Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.



4" Airtight Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.



4" Airtight IC Housing  
New Construction

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket  
New Construction

CAT NO.	SPECIFICATIONS
EL99ICA-G24	Lamp: 18W MAX.



4" Airtight IC 2-Hour Fire Rated Housing  
New Construction


CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

## 4" Accessories



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L