

Project name:	
Fixture type:	
Date:	

4" Reflector with Wall Wash Trim



Features

- Wall Wash with White Scoop.
- Lamp: 32W MAX CFL (PL-T) or 50W PAR20, R20.
- O.D.: 4 3/4".

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options







Clear w/White Trim Gold w/White Trim

All White

Product Numbers

Item	Description	Finish
EL925C		Clear with White Trim
EL925G		Gold with White Trim
EL925W		All White
EL925KC	with Socket Bracket	Clear with White Trim
EL925KW	with Socket Bracket	All White

Product Number Builder Example: EL925C

4" Wall Wash Trim White Scoop Socket Bracket Finish

EL925

no Socket Bracket

K Socket Bracket

Clear with White Trim

G Gold with White Trim

W All White

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing **Double Wall Construction**



4" Airtight Housing **New Construction**



4" Airtight IC Housing **New Construction**

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	
EL99A	

SPECIFICATIONS		
Lamp: 50W MAX.		

SPECIFICATIONS CAT NO. EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket **New Construction**

FA	
PIE.	

4" Airtight IC 2-Hour Fire Rated Housing **New Construction**

CAT NO.	SPECIFICATIONS
FL99ICA-G24	Lamp: 18W MAX.

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

4" Accessories



Fire Cover



Fire Enclosure



M	ca	Fi	re	Ta	ре

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3%"

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L