

Project name:	
Fixture type:	
Date:	

4" Shower Trim with Reflector and Clear Lens



Features

- Shower Trim with Reflector and Clear Lens.
- Lamp: 32W max CFL (PL-T), 40W MAX A19 or 50W MAX PAR20.
- O.D.: 4 3/4".

Technical Details


Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options



Product Numbers

Item	Finish
EL9111B	All Black
EL9111SH	White Lexan
EL9111W	All White

Product Number Builder Example: EL9111B

4" Shower Trim with Reflector and Clear Lens

EL9111

Finish

- B All Black
- **C** Clear
- SH White Lexan
- W All White
- **G** Gold
- **CP** Copper

Compatible Products



For use with 4" Trims for PAR Lamps

4"Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing New Construction




4" Airtight IC Housing New Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99LDICA	Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket New Construction

	-			
FA.		-273D		
PIG.	100	=	-	

4" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL99ICA-G24	Lamp: 18W MAX.	

CAT NO.	SPECIFICATIONS
EL99FICA	Lamp: 35W MAX.

4" Accessories



Fire Cover

Fire Enclosure



Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRECVR	9 ¾" H x 17" O.D.

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow. 16" L x 14 3%" \

CAT NO.	SPECIFICATIONS
FIRETAPE	³ ⁄ ₄ " W × 16' L