

Project name:	
Fixture type:	
Date:	

## **4" Square Reflector Trim**



#### **Features**

- Square Reflector.
- Lamp: 32W MAX. CFL, 50W MAX PAR20 or R20.
- O.D.: 4 3/4" Square.


#### **Technical Details**

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.



#### **Product Numbers**

Item	Description	Finish
EL2999W		All White
EL2999B		Black with White Trim
EL2999C		Clear with White Trim
EL2999BZ		All Bronze
EL2999KW	with Socket Bracket	All White

### Product Number Builder Example: EL2999W

4" Square Reflector Trim Socket Bracket Finish

EL2999

no Socket Bracket **K** with Socket Bracket

W All White

**B** Black with White Trim

C Clear with White Trim

**BZ** All Bronze

# **Compatible** Products



For use with 4" Trims for PAR Lamps

## 4" Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing New Construction




4" Airtight IC Housing New Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO. SPECIFICATIONS

EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket New Construction

	-			
A				
100	40.0	<u></u>	-	

4" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL99ICA-G24	Lamp: 18W MAX.	

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

### 4" Accessories

CAT NO.

**FIRECVR** 



Fire Cover

SPECIFICATIONS

9 3/4" H x 17" O.D.

1	
and the same of th	

Fire Enclosure



CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 %" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L