

Fixture type:	
Date:	

4" Square Shower Trim with Frosted Pinhole Glass



Features

- Square Trim with Frosted Pinhole Glass.
- Lamp: 26W MAX. Triple Tube CFL, 30W MAX R20.
- O.D.: 4 3/4" Square.

Technical Details

Construction: Meticulously manufactured trim with a powder coated or anodized finish.

Installation: Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Housing: Compatible with 4"Line Voltage IC and Non-IC versions.

Lamp: Compatible with Medium base (E26) PAR type.

Options



Bronze

White

Product Numbers

Item	Finish
EL2915BZ	All Bronze
EL2915W	All White

Product Number Builder Example: EL2915BZ

4" Square Trim with Frosted Pinhole Glass

Finish

EL2915

BZ All Bronze

W All White

Compatible Products



For use with 4" Trims for PAR Lamps

4" Line Voltage ICA Housings



4" Airtight IC Housing

Double Wall Construction



4" Airtight Housing New Construction




4" Airtight IC Housing New Construction

CAT NO.	SPECIFICATIONS
EL99ICA	Lamp: 50W MAX.

CAT NO.	SPECIFICATIONS
EL99A	Lamp: 50W MAX.

CAT NO. SPECIFICATIONS

EL99LDICA Lamp: LED 12W MAX.



4" Airtight IC Housing with GU24 Base Socket New Construction

	-			
A				
100	40.0	<u></u>	-	

4" Airtight IC 2-Hour Fire Rated Housing

New Construction

CAT NO.	SPECIFICATIONS	
EL99ICA-G24	Lamp: 18W MAX.	

CAT NO.	SPECIFICATIONS	
EL99FICA	Lamp: 35W MAX.	

4" Accessories

CAT NO.

FIRECVR



Fire Cover

SPECIFICATIONS

9 3/4" H x 17" O.D.

1	
and the same of th	

Fire Enclosure



CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 %" W

Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	¾" W × 16' L