

6" 120/277/347V LED

Recessed Gimbal Downlight

with 5-CCT Switch

Our 6" Dimmable LED Recessed Gimbal Downlight is designed for quick and easy installation without a housing for both new construction and remodel applications, giving you the options you are looking for in one fixture. The manual switch allows you to choose between 2700K, 3000K, 3500K, 4000K or 5000K. IC-Rated for use with direct contact with insulation.




Features

- Adjustable Gimbal offers 25° tilt range
- IC Airtight for use with direct contact to insulation.
- Lumens (Wattage): 900 lm (15W)
- Designed to fit in plenums as shallow as 3".
- Eliminates the need for housing.
- New Construction application requires mounting plate or frame.
- Remodel applications require no additional accessories.
- Wet Location allows for use indoors or outdoors.
- ETL listed
- Includes driver and Jbox.

Specifications

Wattage	15W
Lumens	900 lm
Voltage	120/277/347V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	0-10V/Triac/ELV
Lamp Type	LED
CRI	90+
Damp Location	Listed

Dimensions



Technical Details

- Optics:** Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.
- Construction:** IC-rated driver and fixture are tested and approved for direct contact with insulation. Aluminum die-cast trim ring with durable powder coat finish preventing rust and paint cracking. Plenum-rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pry out.
- Installation:** Designed for super shallow ceiling plenums without any housing. High-strength steel spring clip for easy installation. Maximum hole size should not exceed 6 1/4" for this product. Suitable installation for t-grid and drop ceiling applications.
- Electrical:** Driver connects directly to 120/277/347V power supply. Standard input wattage is 15W, 60 lumens per watt.
- Dimmability:** Works with 120/277/347V dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatibility List.
- Listings:** ETL Listed for Damp Locations. IC-Rated for direct contact with insulation. Air Tight certified in accordance with ASTM E283-2004.
- Warranty:** 5-year limited warranty.

Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ERT613CT5DXW	LED	900 lm	2700K, 3000K, 3500K, 4000K, 5000K	15W	120/277/347V	0-10V/Triac/ELV	All White