

# 6" Pex™ Round Reflector Trim for Koto Module

Pex™ 6" diecast Round Reflector Trim. One-piece trims with twist-on system for easy tool-free installation. For use with Koto LED Module.



## Features

- 6" Round Reflector
- Convenient twist-lock design for ease of installation.
- For Wet location
- Lamp: Koto LED Module.
- O.D.: 7 1/2".

## Specifications

**Wet Location** Listed

## Technical Details

**Construction:** Diecast aluminum with a powder coated finish.

**Installation:** Twist-lock design allows for easy mounting onto the Koto™ LED Module. Torsion springs securely mount trim into the housing and keeps ring flush with ceiling.

**Compatible Housing:** Compatible with 6" Koto Housings.

**Lamp:** Koto™ LED Module

## Options



White



All Black




All Bronze




Haze w/White Trim

## Dimensions



## Trim w/Module



Product Numbers

Item	Finish
ELK6418W	All White
ELK6418BB	All Black
ELK6418BZ	All Bronze
ELK6418H	Haze with White Trim

Product Number Builder    Example: ELK6418W

6" Pex™ Round Reflector Trim for Koto Module

Finish

ELK6418


- W All White
- BB All Black
- BZ All Bronze
- H Haze with White Trim

# Compatible Products

For use with 6" Koto™ Twist-On Trims



## Koto™ LED Module



**Koto™ LED Module**  
ELK07, ELK09, & ELK11

### PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
07	750 lm	27 2700K	(blank) 38° lens (Standard)
09	950 lm	30 3000K	-S 18° lens
11	1150 lm	35 3500K	-N 25° lens
		40 4000K	-W 60° lens
		SD Sunset Dimming (For ELK09 & ELK11)	-FC 18° - 50° Adjustable (ELK07 Only)

### ACCESSORIES



#### Lens

**EP731C** 18° Lens  
**EP732C** 25° Lens  
**EP733C** 38° Lens  
**EP734C** 60° Lens  
\*EP732C, EP733C, EP734C  
Included with standard module

#### Snoot


**L50W** White  
**L50B** Black



#### Secondary Optics

**L45** Hex Louver  
**L46** Linear Lens  
**L47** Spread Louver  
**L49** Frosted Lens  
**L51** Color Shifter  
**L57** White Hex Louver  
**L52** Blue Lens  
**L53** Pink Shifter

\*Standard module includes 38° installed  
with 25° & 60° field changeable lenses.




**Koto™ LED Module  
with 5-CCT Switch**



#### Product Number

**ELK08CT5** 825 lm, 5-CCT, 120V  
**ELK10CT5** 1000 lm, 5-CCT, 120V




**12V AC Retrofit  
Koto™ LED Module**

For retrofitting 4" Bi-Pin  
12V AC GU5.3 Housings

#### Product Number


**ELK0827-12** 800 lm, 2700K, 12V AC  
**ELK0830-12** 800 lm, 3000K, 12V AC  
**ELK08SD-12** 800 lm, Sunset, 12V AC

## 6" Koto™ Dedicated LED ICA Housings



**6" Standard ICA Housing**  
**New Construction**

CAT NO.	SPECIFICATIONS
EL770ICA	7" Height
EL760ICA	5 ½" Height, Shallow



**6" Standard Remodel ICA Housing**  
**Remodel**

CAT NO.	SPECIFICATIONS
EL770RICA	7 ½" Height
EL760RICA	5 ½" Height, Shallow



**6" 2-Hour Fire Rated ICA Housing**  
**New Construction**


CAT NO.	SPECIFICATIONS
EL76FICA	7 ¾" Height - Sound Rated
EL75FICAS	6 ¾" Height, Shallow

# Compatible Products

For use with 6" Koto™ Twist-On Trims



## Koto™ Architectural LED Light Engine



Koto™ LED Light Engine  
ELK19 - ELK21

PRODUCT NUMBER BUILDER				
Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle	
ELK				
19	750 - 850 lm	27D 2700K	(blank)	38° lens (Standard)
21	1100 - 1500 lm	30D 3000K	-S	18° lens
		35D 3500K	-N	25° lens
		40D 4000K	-W	60° lens
		SD Sunset Dimming (ELK19 Only)	-FC	18° - 50° Adjustable (ELK21 Only)

*\*Standard module includes 38° installed with 25° & 60° field changeable lenses.*

### ACCESSORIES



#### Lens

EP731C 18° Lens  
EP732C 25° Lens  
EP733C 38° Lens  
EP734C 60° Lens  
\*EP732C, EP733C, EP734C  
Included with standard module



#### Snoot


L50W White  
L50B Black



#### Secondary Optics

L45 Hex Louver  
L46 Linear Lens  
L47 Spread Louver  
L49 Frosted Lens  
L51 Color Shifter  
L57 White Hex Louver  
L52 Blue Lens  
L53 Pink Shifter

## 6" Koto™ Dedicated LED ICA Housings



6" Koto™ Maximum Adjustability ICA Housing  
850 lm (14.7W) w/ELK19 Series Module  
1100 lm (14.7W) w/ELK21 Series Module  
**New Construction**

CAT NO.	SPECIFICATIONS
E6LK37ICA	7 ½" Height, Triac/ELV, 120V
E6LK38ICAD	7 ½" Height, 0-10V/Triac/ELV, 120/277V



6" Maximum Adjustability High Lumen ICA Housing  
Use with ELK21 Series Module  
Not for use with ELK19 Series Module  
**Double Wall**


CAT NO.	SPECIFICATIONS
E6LK43ICA	7 ¼" Height, 120V, Triac/ELV, 1250 lm
E6LK44ICAD	7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1250 lm
E6LK56ICA	7 ¼" Height, 120V, Triac/ELV, 1500 lm
E6LK57ICAD	7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1500 lm

# Compatible Products

For use with 6" Koto™ Twist-On Trims



## Koto™ 24V DC LED Light Engine



24V DC Koto™ LED  
Light Engine

### PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Voltage
ELK			
	08 800 lm	27 2700K 30 3000K	-24 24V DC

*\*Standard module includes 38° installed with 25° & 60° field changeable lenses.*

### ACCESSORIES



#### Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens
<i>*EP732C, EP733C, EP734C Included with standard module</i>	



#### Snoot

L50W	White
L50B	Black



#### Secondary Optics


L45	Hex Louver	L57	White Hex Louver
L46	Linear Lens	L52	Blue Lens
L47	Spread Louver	L53	Pink Shifter
L49	Frosted Lens		
L51	Color Shifter		

## 6" Koto™ Dedicated LED ICA Housings (24V DC Input)



24V DC 2-Hour Fire Rated 6" ICA Housing  
New Construction

CAT NO.	SPECIFICATIONS
E24V76FICA	7 3/4" Height <i>*Requires 24V DC Transformer</i>




24V DC 6" Standard ICA Housing  
New Construction

CAT NO.	SPECIFICATIONS
E24V770ICA	7 1/2" Height
E24V770ICA-EM5	Battery Backup, 24W MAX. <i>*Requires 24V DC Transformer</i>




24V DC 6" Standard ICA Housing  
Remodel

CAT NO.	SPECIFICATIONS
E24V770RICA	7 1/2" Height <i>*Requires 24V DC Transformer</i>



24V DC 2-Hour Shallow Fire Rated 6" ICA  
New Construction Housing

CAT NO.	SPECIFICATIONS
E24V75FICAS	6 3/16" Height <i>*Requires 24V DC Transformer</i>



24V DC 6" Shallow ICA Housing  
New Construction

CAT NO.	SPECIFICATIONS
E24V760ICA	5 1/2" Height
E24V760ICA-EM5	Battery Backup, 24W MAX. <i>*Requires 24V DC Transformer</i>



24V DC 6" Shallow ICA Housing  
Remodel

CAT NO.	SPECIFICATIONS
E24V760RICA	5 1/2" Height <i>*Requires 24V DC Transformer</i>