

Birch™ 6" Round Adjustable Reflector Trim

The sleek and clean looking Birch™ System Trims will blend seamlessly into your commercial space. The trims offer a light source aperture of 2 5/8" and a deep reflector that delivers smooth and abundant light distribution with minimal glare.



Features

- Self-flanged spun aluminum adjustable reflector
- Twist-On system for easy installation to Birch™ Modules
- Spring loaded mounting clips to hold them tightly into the ceiling
- Compatible with Birch Pro LED Module (ELB15RCT5ICA) and Birch High Lumen LED Module (ELB30 Series)

Technical Details

Installation: Easy to install with Twist-On mechanism to any of our Birch System modules. Spring loaded mounting clips will hold the trim tightly into the ceiling.

Warranty: ELCO Products are built to last. 5-year Limited warranty.

Options



White




All Haze (semi-specular)



Black

Dimensions



Product Numbers

Item	Finish
ELB629W	All White
ELB629B	All Black
ELB629H	All Haze (Semi-Specular)

Product Number Builder Example: **ELB629W**

Birch™ 6" Round Adjustable Reflector Trim

Finish


ELB629

- W** All White
- B** All Black
- H** All Haze (Semi-Specular)

Compatible Products


For use with **Birch™ Trims**

Birch™ LED Modules




Birch™ Pro LED Module with 5-CCT Switch (750 lm - 1500 lm)

CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB15RCT5ICA	5-CCT Switch 2700K, 3000K, 3500K, 4000K, 5000K	<ul style="list-style-type: none"> • IC Rated, for use in IC and Non-IC applications • 750 lm - 1500 lm (10W - 20W) • Beam Angle adjustment from 25°-45° • 120/277V input with 0-10V dimming



Birch™ High Lumen LED Module (1250 lm - 3000 lm)


CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB30R30	3000K	<ul style="list-style-type: none"> • Non-IC, for use in Non-IC applications • 1250 lm - 3000 lm (13W - 30W)
ELB30R35	3500K	<ul style="list-style-type: none"> • Beam Angle adjustment from 22°-50°
ELB30R40	4000K	<ul style="list-style-type: none"> • 120/277V input with 0-10V dimming




Birch™ High Lumen LED Module (3200 lm - 5000 lm)

CAT NO.	COLOR TEMPERATURE	SPECIFICATIONS
ELB50R30	3000K	<ul style="list-style-type: none"> • Non-IC, for use in Non-IC applications • 3200 lm - 5000 lm (32W - 55W)
ELB50R35	3500K	<ul style="list-style-type: none"> • Beam Angle adjustment from 22°-50°
ELB50R40	4000K	<ul style="list-style-type: none"> • 120/277V input with 0-10V dimming • Works with 6" & 8" Trims (ELB610 & ELB810 only) • Not compatible with ELB410, ELB440, & ELB629 trims


4", 6", & 8" Birch™ Architectural Frames



4" Architectural Commercial Frame
New Construction



6" Architectural Commercial Frame
New Construction




8" Architectural Commercial Frame
New Construction

CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS	CAT NO.	SPECIFICATIONS
ELB4EH	Frame (hanger bars required)	ELB6EH	Frame (hanger bars required)	ELB8EH	Frame (hanger bars required)
ELB4EH-EM5	with Emergency Backup	ELB6EH-EM5	with Emergency Backup	ELB8EH-EM5	with Emergency Backup

Hanger Bars for **Birch™** Architectural Frames


27" **Flat Hanger Bars** for Wood Construction

CAT NO.	SPECIFICATIONS
FB27	Set of 2



26" **C-Channel Hanger Bars** for T-Bar Ceilings

CAT NO.	SPECIFICATIONS
CH26	Set of 2




Compatible Products




For use with **Birch™ Trims**


4", 6", & 8" Birch™ Plaster Frames



4" Plaster Commercial Frame
New Construction



6" Plaster Commercial Frame
New Construction



8" Plaster Commercial Frame
New Construction

CAT NO.	SPECIFICATIONS
ELB4PF	Frame
ELB4PF-EM5	with Emergency Backup


CAT NO.	SPECIFICATIONS
ELB6PF	Frame
ELB6PF-EM5	with Emergency Backup

CAT NO.	SPECIFICATIONS
ELB8PF	Frame
ELB8PF-EM5	with Emergency Backup

Remodel & Retrofit Birch™ Applications

Remodel/Retrofit

CAT NO.	SPECIFICATIONS
ELBRMD	Remodel
ELBRMD-EM5	with Emergency Backup



Retrofit

CAT NO.	SPECIFICATIONS
ELBRT	Retrofit

