

Project name:	
Fixture type:	
Date:	

Ixia™ LED Low Voltage Undercabinet Lightbar



Features

- CCT Tunable (3000K-6500K)
- Linkable up to 12 ft.
- Polycarbonate lens
- Aluminum finish
- Input 24VDC
- Dimmable with EUDCCT/EUDS1
- Mounting brackets included
- 5/8" H x 3/4" W

Specifications

4.5W
260 lm
24 VDC
3000K
EUDS1
LED

Product Number

Item	Description	Lamp type	Lumens	ССТ	Watts	Voltage	Dimming	Finish
EUN55W	12"	LED	260 lm	3000K	4.5W	24 VDC	EUDS1	Aluminum

Compatible Products

Ixia® LED Undercabinet Light



Accessories



LED CCT Controller and Dimmer

CAT NO.	SPECIFICATIONS	
EUDCCT	For EUN51-EUN53 only	



Linking Cable

CAT NO.	SPECIFICATIONS	
EUDC51	For EUN51-EUN56	



Dimmer Switch

CAT NO.	SPECIFICATIONS	
FUDS1	For FUN54-FUN56 only	



PIR Sensor Switch

CAT NO.	SPECIFICATIONS	
EUDPH1	For EUN54-EUN56 only	



Movement Sensor Switch

CAT NO.	SPECIFICATIONS
EUDMS1	For EUN54-EUN56 only



Input Connector

CAT NO.	SPECIFICATIONS	ı
EUDPC	For EUN54-EUN56 only	



24V LED Driver with 6-Way Distributor

CAT NO.	SPECIFICATIONS	
DRV24V30W	For EUN51-EUN56	



Dimmer Compatibility Chart Undercabinet

EUD Series

For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
120V Only			
Legrand	CFL/LED Multi-way Paddle Dimmer	HDCL-453	10% - 100%
Leviton	IllumaTech Single Pole/3-Way Preset Electro-Mechanical Electronic Low Voltage Slide Dimmer	IPE04	10% - 100%
	Decora SureSlide® Single Pole/3-Way with Present ON/OFF Switch	6674	5% - 90%
	Rotary Dim N Glo 600W 3-Way Dimmer	DNG-603PH	10% - 100%
	DIVA® (Gloss) 450W, Single Pole, Magnetic Low Voltage Dimmer	DVLV-600P	10% - 100%
Ludana	DIVA® Series 600W Single Pole Dimmer	DV-600P	10% - 100%
Lutron	DIVA® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	5% - 86%
	Maestro® Series 150W Single Pole/3-Way/Multi-Location Dimmer	MACL-153M	5% - 80%
	DIVA® (Gloss) 600W 3-Way Preset Eco-dim Dimmer	DV-603PG	10% – 100%

^{*}NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com