HOUR FIRE RATED

HOUR FIRE RATED

ELCO Lighting



Fire Rated Items In Stock!



UL listed to maintain fire ratings up to 2 hours. For use in insulated ceilings. Integrated non-combustible insulation enhances acoustical protection, dampening sound transfer between floors. Housing Meets Restricted Air Flow Requirements (per ASTM E-283). Quick Connect terminal connector for easy installation. Meets Title 24 Requirements.



NEW 6" LED <u>Shallow</u> Fire Rated ICA New Construction Housing

EL75FICAS

- 24W MAX.
- 2-Hour Fire Rated housing
- 120/277V, 60Hz
- For use in insulated ceilings
- Meets Title 24 High Efficacy requirements
- Housing Meets Restricted Air Flow requirements (per ASTM E- 283)
- UL Listed for damp locations
- UL Listed for wet locations
- Height: 6 1/4"



NEW 4" LED Fire Rated ICA New Construction Housing

EL48FICA

- 14W MAX.
- 2-Hour Fire Rated housing
- 120/277V, 60Hz
- For use in insulated ceilings
- Meets Title 24 High Efficacy requirements
- Housing Meets Restricted Air Flow requirements (per ASTM E- 283)
- UL Listed for damp locations
- UL Listed for wet locations
- Height: 6 %"

NEW 4" LED Shallow Fire Rated ICA New Construction Housing

EL492FICAS

- 14W MAX.
- 2-Hour Fire Rated housing
- 120/277V, 60Hz
- · For use in insulated ceilings
- Meets Title 24 High Efficacy requirements
- Housing Meets Restricted Air Flow requirements (per ASTM E- 283)
- UL Listed for damp locations
- UL Listed for wet locations
- Height: 4 %"

Subject to US tariffs. All other standards, terms and conditions apply.

Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com

E-mail your order to: orderdesk@elcolighting.com Tel: 800.522.2626 • Fax: 800.644.2626

