# NEW LED Items in Stock!

### **LED Windsor**<sup>™</sup>

- To be used with 120V single or two circuit track.
- Diecast aluminum fixture with integrated driver.
- 42° Standard beam angle, 20° lens included.
- 90° tilt, 358° rotation.
- 50,000 hours life-span
- 7 1/8" H x 4 3/8" L x 3 1/8" O.D.

## 10W / 700 lm / 3000K

ET74830W White ET74830B Black

17W / 1050 lm / 3000K

ET74730DW White
ET74730DB Black



### EE71LD


- Emergency lighting solution to keep exit routes safe and illuminated.
- (2) 1W LED glare free light heads
- 120/277V
- 90 minutes of emergency operation
- · Sturdy thermoplastic housing
- Suitable for wall and ceiling mount
- Test switch and battery charging indicator
- UL listed for damp locations
- 8 %" W x 4 ½" H x 2" D






# **Moa™ Adaptive Mini LED Step Lights**

- 2.5W / 50 lm / 3000K
- Adaptive diecast aluminum faceplate design for Vertical or Horizontal mounting orientation.
- Mounts in standard single gang box.
- Integrated LED board and driver with diffused lens behing faceplate.
- Wet location listed for indoor use
- IC rated for direct contact with insulation
- 50,000 hours life-span





ELST9930W	White
ELST9930B	Black
ELST9930N	Nickel
ELST9930BZ	Bronze

Subject to US tariffs. All other standards, terms and conditions apply. Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com