ELCO Lighting

2042 E. Vernon Ave. Vernon, CA 90058 www.elcolighting.com Form #0274 10.19

The Ply[™] System **0-10V LED Inserts & Housings**

- 0-10V Dimmable
- 120/277V driver
- 93+ CRI for extremely accurate color rendering
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- Deep set LED trim reduces glare while providing even illumination
- CA Title 24, ETL listed, JA8-2016-E
- ENERGY STAR
- Life span of 50,000 hours L70



• 12W

• 5 ½" OD



6" LED 0-10V Inserts

• 20W

All White

Haze/Wht Ring

• 7 1/2" O.D.

EL69530DW



3000K/1350 lm 3500K/1425 lm 4000K/1500 lm

EL69535DW

EL69530DHW EL69535DHW EL69540DHW

.....

Chrome/Wht Ring EL69530DCW EL69535DCW EL69540DCW

	3000K/800 lm	3500K/850 lm	4000K/900 lm
All White	EL49530DW	EL49535DW	EL49540DW
Haze/Wht Ring	EL49530DHW	EL49535DHW	EL49540DHW
Chrome/Wht Ring	EL49530DCW	EL49535DCW	EL49540DCW

0-10V Dedicated LED | • 0-10V Dimmable IC Airtight Housings

• 120/277V input

(per ASTM E-283)



2-Hour Fire Rated IC Airtight Housings

4" LED Housing **EL49FICDXA** 4" Shallow LED Housing EL492FICDXAS

6" LED Housing **EL76FICDXA**



New Construction IC Airtight LED Housings

4" LED Housing EL490ICDXA 4" Shallow LED Housing EL492ICDXA

6" LED Housing EL760ICDXA

Meets restricted air flow requirements
IC Rated for direct contact with insulation

EL69540DW

CA Title 24, ETL listed, JA8-2016-E



Remodel **IC Airtight LED Housings**

4" LED Housing **EL490RICDXA** 4" Shallow Housing EL492RICDXA

6" LED Housing **EL760RICDXA**

Subject to US tariffs. All other standards, terms and conditions apply. Please provide your e-mail address to salesadmin@elcolighting.com. To unsubscribe e-mail: salesadmin@elcolighting.com

E-mail your order to: orderdesk@elcolighting.com Tel: 800.522.2626 • Fax: 800.644.2626

