

# ELCO LIGHTING

Form #0188\_02.16

2042 E. VERNON AVE  
VERNON, CA 90058  
sales@elcolighting.com

TEL: (323) 231-2600  
FAX: (323) 231-3200  
www.elcolighting.com

## New LED Items In Stock!

Introducing ELCO's LED Outdoor Lighting designed to enhance security and safety for building exteriors, parking garages, walkways and other outdoor locations. Constructed with die-cast aluminum with dark bronze power coated finish.

These fixtures utilized the most energy efficient LED technology. UL listed. 50,000 Hours/5 Year Extended Warranty.

### Full Cut-Off Wall Pack

- For mounting over electrical box or directly to the wall (surface conduit supply)
- 120V/277V AC
- Clear glass lens
- Equipped with gauged arm for 5°, 10°, 15°, and 20° tilt
- Built-in 120V photocell (for 277V supply photocell must be replaced with EWPPH2)
- 6 3/4"L x 4 1/8"H x 9"W



**EWP20C50** 20W, 5000K, 2000 lm, CRI≥70

**EWP30C50** 30W, 5000K, 3000 lm, CRI≥70

**EWP40C50** 40W, 5000K, 4000 lm, CRI≥70

### Medium Wall Pack

- For mounting over electrical box or directly to the wall (surface conduit supply)
- 120V/277V AC
- Polycarbonate lens
- DLC qualified when used with EWPM5H shield
- 14 1/4"L x 9 1/4"H x 7 3/8"W



**EWP45M40** 45W, 4000K, 3700 lm, CRI≥80

**EWP45M50** 45W, 5000K, 3800 lm, CRI≥80

**EWP70M40** 70W, 4000K, 5610 lm, CRI≥80

**EWP70M50** 70W, 5000K, 6000 lm, CRI≥80

### Canopy

- For mounting over electrical box or directly to the ceiling (surface conduit supply)
- 120V/277V AC
- Polycarbonate lens
- 9 3/4"L x 2 7/8"H



**ECP45M40** 45W, 4000K, 4000 lm, CRI≥75

**ECP45M50** 45W, 5000K, 4050 lm, CRI≥75

**ECP70M40** 70W, 4000K, 5700 lm, CRI≥75

**ECP70M50** 70W, 5000K, 5900 lm, CRI≥75

### Large Wall Pack

- For mounting over electrical box or directly to the wall (surface conduit supply)
- 120V/277V AC
- Polycarbonate lens
- DLC qualified when used with EWPLSH shield
- 18"L x 9 3/4"H x 8 3/4"W



**EWP90L40** 90W, 4000K, 7500 lm, CRI≥80

**EWP90L50** 90W, 5000K, 7700 lm, CRI≥80

**EWP135L40** 135W, 4000K, 11200 lm, CRI≥80

**EWP135L50** 135W, 5000K, 11500 lm, CRI≥80

### Photocell Wall Mount

- For mounting over electrical box or directly to the wall (surface conduit supply)
- 120V/277V AC
- Polycarbonate lens
- Built-in 120V photocell (for 277V supply photocell must be replaced with EWPPH2)
- 3 1/2"L x 8 3/8"H



**EWM17W30** 17W, 3000K, 1500 lm, CRI≥80

**EWM17W40** 17W, 4000K, 1600 lm, CRI≥80

**EWM25W30** 25W, 3000K, 2000 lm, CRI≥80

**EWM25W40** 25W, 4000K, 2100 lm, CRI≥80

### Accessories for Medium and Large Wall Packs:



#### Wall Pack Shield

**EWPM5H** For Medium Wall Pack

**EWPLSH** For Large Wall Pack



#### Photocell for Wall Packs (Medium & Large)

**EWPPH1** 120V

**EWPPH2** 277V

• CALL YOUR LOCAL REPRESENTATIVE FOR PRICING •

Please provide your e-mail address to [salesadmin@elcolighting.com](mailto:salesadmin@elcolighting.com)

To unsubscribe e-mail: [salesadmin@elcolighting.com](mailto:salesadmin@elcolighting.com)

All other standards, terms and conditions apply.